



DC-2000 Lever Arm 60 to 80 Kgs

- Extruded Aluminium Alloy Housing Precision Machined & Finished
- · Two Speed Controls For Approch & Latching
- · Jerk-free, Smooth Operation Controlled by Rack & Pinion Mechanism
- · Suitable for Wooden & Metal Framed Doors
- · Suitable for On Door & On Frame installation
- · Universal Mounting for Left & Right Hand Doors without adjustment
- Adjustable Lever Arm for degree Adjustment

Technical Specifications

Door Weight Up to 80 Kgs. Door width Up to 1100mm Door Height Up to 2100mm. Finish PU Painted Dimensions (mm) L202 x W40 x H55

Order Information

Code Colour DC-2000-LA-PU SR Silver DC-2000-LA-PU BLK Black DC-2000-LA-PU BN Brown DC-2000-LA-PU GD Gold







DC-2000 FC Lever Arm 60 to 80 Kgs

- Extruded Aluminium Alloy Housing Body Preciously Machined & Finished.
- · Two Speed Control For Approch & Latching.
- Jerk Free, Smooth Operation Controlled by Rack & Pinion Mechanism.
- Suitable For On -Door & On Frame Installation.
- Universal Mounting For Left & Right Hand Doors Without Adjustment.
- Adjustable Lever Arm For Degree Adjustment.
- Specially Designed considering Lower Ceiling Level For speed Adjustment.
- Available with Pelmet option also.

Technical Specifications

Door Weight Up to 80 Kgs. Door width Up to 1100mm Door Height Up to 2100mm. Finish PU Painted Dimensions (mm) L202 x W40 x H55

Order Information

Code Colour DC-2000-FC LA-PU SR Silver DC-2000-FC LA-PU BLK Black DC-2000-FC LA-PU BN Brown DC-2000-FC LA-PU GD Gold



DC-2500 / DC-2600 Palmet Door Closer 60 to 80 Kgs

- Extruded Aluminium Alloy Housing Precision Machined & Finished
- Aluminium Extruded Pelmet Ann Mounting for Elegant & Compact Looks
- Two Speed Control For Approach & Latching.
- · Jerk Free, Smooth Operation Controlled by Rack & Pinion Mechanism
- · Universal Mounting for Left & Right Hand Doors without adjustment
- · Suitable for Wooden & Metal Framed Doors

Technical Specifications

Door Weight Up to 80 Kgs. Door width Up to 1100mm Door Height Up to 2100mm. PU Painted Finish

Order Information

Code Colour DC-2500-PA-PU SR DC-2600 HPA-PU SR Silver DC-2500-PA-PU BLK DC-2600 HPA-PU BLK Black DC-2500-PA-PU BN DC-2600 HPA-PU BN Brown Dimensions (mm) L202 x W40 x H55 DC-2500-PA-PU GD DC-2600 HPA-PU GD

STERLING

The Trusted name for Quality Product. We believe on Quality and Customer Satisfaction





FS-3000 UV - SSM - GF

- · Aluminium Pressure Die cast Housing.
- · Slim & Compact Size.
- Light Weight for easy handing (3.5 Kgs).
- Two Speed Controls.
- Buit in Hold open at 90°
- Back Check to Prevent Door & Wall Damage.
- · Adjustable Closing Strength.
- · Suitable for Glass Door.

Technical Specifications

Door Weight Up to 120 Kgs. Door width Up to 1100mm (3¾ ft.) Door Height Up to 2100mm (7 ft.)

Finish MATT

Box Dimensions (mm) L275 x W82 x H54

Order Information

Code Colour FS-3000-UV-SSM Stainless

Steel-Matt

Silver



FS-3000 UV - SSM - WF

- · Aluminium Pressure Die cast Housing
- Slim & Compact Size
- Light Weight for easy handing (3.5 Kgs)
- · Two Speed Controls
- Buit in Hold open at 90°
- · Back Check to Prevent Door & Wall Damage
- Adjustable Closing Strength
- Suitable for Wooden Door

Technical Specifications

Door Weight Up to 120 Kgs. Door width Door Height

Up to 1100mm (3¾ ft.) Up to 2100mm (7 ft.)

Finish MATT

Box Dimensions (mm) L275 x W82 x H54

Order Information

Colour

FS-3000-UV-SSM Stainless

Steel-Matt

Silver

OUR VISION

To compete with the world players and facilitate the Indian housing and commercial needs in the arena of architectural hardware products along with a complete range of fittings solutions, by 2017 so as to be a most reliable player and facilitator for architectural hardware needs in India and across the globe.

OUR MISSION

necessary door closers, handles, locks & accessories, when installed, provide the proper functionality of assembly, operation, security & handiness to a door.

To be a partner of choice in architectural hardware products & fittings for every selected area in residential & commercial projects so as to be a major partner in the development of our clients across the globe.

DISTRIBUTORS / DEALERS

NOBLE TRADERS

Plot No. 56/P, Kalpana Housing Society, Chintal, Quthbullapur, Hyderabad - 500054.

Phone: +91 - 9966747318 Email: sales@nobletraders.in





DC-2900 LA HD 80 to 100 Kgs.

- Extruded Aluminium Alloy Housing, Body Preciously Machined
 & Finished
- Two Speed Controls for Approch & Latch in
- · Jerk-free, Smooth Operation Controlled by Rack & Pinion Mechanism
- Suitable for Wooden & Metal Framed Doors
- · Suitable for On Door & On Frame installation
- · Universal Mounting for Left & Right Hand Doors without adjustment

Technical Specifications

Door Weight Up to 100 Kgs.

Door width Up to 1100 mm

Door Height Up to 2100 mm

Finish PU Painted

Dimensions (mm) L225 x W40 x H55

Order Information

 Code
 Colour

 DC-2900 - LA PU SR
 Silver

 DC-2910 - PA PU SR
 Silver

 DC-2920 - HPA PU SR
 Silver

Silver

Silver

Brown

Gold



DC-1500 Alu Eco For 40-55 Kgs.

- Extruded Aluminium Alloy Housing Body Preciously Machined & Finishing.
- · Two Speed Control For Approach & Latching.
- Jerk Free, Smooth Operation Controlled by Rack & Pinion Mechanism.
- Slim Compact Design for Easy to Installation & User Friendly.
- Suitable for On door & On Frame Installation.
- Less Mounting Hole Distance Designed Considering Limited Space of Aluminium Section.
- · Universal Mounting For Left and Right Hand Door.
- · Suitable for Wooden, Metal & Aluminium Doors.

Technical Specifications

Door Weight Up to 55 Kgs.

Door width Up to 1100 mm
(For Aluminium Door & 970 mm for Wooden Door.)

Door Height Up to 2100 mm

Finish PU Painted

Dimensions (mm) L203 x W39 x H40

Order Information

 Code
 Colour

 DC-1500 - LA PU SR
 Silver

 DC-1500 - LA PU BN
 Brown

 DC-1500 - LA PU GD
 Gold

 DC-1510 - PA PU SR
 Silver

 DC-1510 - PA PU BN
 Brown

 DC-1520 - HPA PU BN
 Brown

 DC-1520 - HPA PU BN
 Brown



DC-750 Capsule LA For 35 kgs

- · Extruded Aluminium Alloy Hosing Body Preciously Machined & Finishing.
- Two Speed Control for Approch & Latching.
- · Jerk Free, Smooth Operation Controlled Rack & Pinion Mechanism.
- · Slim Compact Design For very light doors.
- Suitable For On door & On Frame Installation.
- Less Mounting Hole Distance Designed Considering Limited Space of Aluminium Section.
- · Universal Mounting For Left & Right Hand Door.
- · Suitable for Aluminum Doors.

Technical Specifications

Door Weight Up to 35 Kgs.

Door width Up to 970 mm
(For Aluminium Door)

Door Height Up to 2100 mm

Finish PU Painted Silver

Dimensions (mm) L185 x W35 x H35

Order Information

Code	Colour
DC-750 - LA PU SR	Silver
DC-750 - LA PU BN	Brown
DC-750 - LA PU GD	Gold







DC-2700 Hold Open Concealed Door Closer For 40-55 Kgs

- Extruded Aluminium Alloy Hosing Body Preciously Machined and Finishing.
- · Two Speed Control For Both Sides.
- Jerk Free, Smooth Operation Control By Rack & Pinion Mechanism.
- · Suitable For Left and Right Hand Door Opening.
- · Leak Proof Design.
- Very Slim Design With 28.00 mm Thickness For Door Width of 32.00 mm
- · Chrome Platted Mounting Strip.
- · Suitable for Wooden & Metal Doors

Technical Specifications

Door Weight Up to 55 Kgs.
Door width Up to 970 mm
Door Height Up to 2100 mm.
Finish PU Painted
Dimensions (mm) L202 x W28 x H50

Order Information

CodeColourDC-2700- PA - PU SRSilverDC-2720- HPA - PU SRSilver

Silver



DC-2800 Hold Open Concealed Door Closer For 60-80 Kgs.

- Extruded Aluminium Alloy Hosing Body Preciously Machined & Finishing.
- Two Speed Control For Both Sides.
- · Jerk Free, Smooth Operation Control By Rack & Pinion Mechanism.
- · Suitable For Left & Right Hand Door Opening.
- · Leak Proof Design.
- Very Slim Design With 31.00 mm Thickness For Door Width of 40.00 mm
- · Chrome Platted Mounting Strip.
- · Suitable for Wooden & Metal Doors

Technical Specifications

Door Weight Up to 80 Kgs.
Door width Up to 1100 mm
Door Height Up to 2100 mm
Finish Up Painted
Dimensions (mm) L210 x W32 x H50

Order Information

CodeColourDC-2800 PA-PUSRSilverDC-2820 HPA-PUSRSilver

Silver



HP 1000 Free Closing Hydraulic Patch For 80 kgs. for Glass Doors

- Aluminium extruded housing body Preciously Machined & Finished enclosed with SS304 cover.
- · Suitable for Door thickness 8 to 15 mm.
- Easy Installation with ± 3 mm in Back Forward & Left
- Right direction adjustment.
- Very Slim & Compact Design with cam & Follower Mechanism.
- · Quick and Easy Installation.

Technical Specifications

Door weight Up to 80kgs.

Door width Up to 1000mm

Door Height Up to 2100mm.

Finish Matt Finish.

Dimensions (mm) L186 x W36 x H68

Order Information

Code Colour HP-1000-UV-SSM SS Matt

Silver